

Hansun Engineer Co., Ltd.

Busan

South Korea

Kiwa Nederland B.V. hereby declares that the
**Fuel System Component for Compress Natural Gas
Power Vehicles Type “Filter series SFT”**

Described in appendix to this declaration complies with the
NGV 3.1-2012 (second edition):

Part 1: General requirements

Part 2: General test methods

Part 18: Filter

Part 19: Fitting

Paul Dijkhof,
Project Manager Automotive Systems



Number
Issued

126841AUT15 Ext.:00
July 21st, 2014

This declaration is issued on July 21st, 2014 and is valid
for the tested products only until the product is modified.
All details of the modifications can be found in the report.

Page

1-1

Appendix to declaration no. 126841AUT104

Appendix no.: 1
Dated: 21 July 2014
Examination report(s):
126841 dated July 2014

Type break down (including specifications):

Hansun Engineering Co., Ltd. Filter series SFT

Make(s):	Hansun Engineering Co., Ltd		
Type(s):	Filter series		
Approval number(s):	R110: E4-110R-010334 ISO15500: 126841MECH104 NGV3.1: 126841AUT15		
Working pressure:	R110:	26MPa (Class 0)	
	ISO 15500:	26 MPa	
	NGV3.1	24.8MPa (3600Psi)	
Temperature range:	-40°C up to 120°C (-40°F up to 248°F)		
Material(s)	Stainless steel (ASTM A276/479 TP316/316L)		
Possible connections:	Tube O.D. Size:		
	Metric: 6mm ~ 12mm		
	Inch: 1/8" ~ 1/2"		
	Pipe Thread: 1/8" ~ 1/2"		